BASICS OF PETROLEUM REMEDIATION - 101

Lance I. Robinson, PE

November 6, 2009



REMEDIATION PROCESS

- Assessment
- Design
- Installation
- Operation
- Monitoring
- Closure




ASSESSMENT PROCESS

- Identify Sources
- Define Horizontal And Vertical Extent Of All Contamination
 - Free Product
 - Soil
 - Water (Groundwater And Surface Water)
 - Vapors
- Know The Regulations
- On Site Days To Weeks In Phases
- Total Duration Of Months To Years



IDENTIFY SOURCES





FLORIDA'S UNIQUE HYDROGEOLOGY

2

3

IACTEC

- 1 Surficial, Sand and Gravel Aquifers Water table typically <100 feet
- 2 Surficial and Floridan Aquifers Water table typically <100 feet
- 3 Surficial, Hawthorne and Floridan Aquifers Water table typically <60 feet
- 4 Surfical and Floridan Aquifers Water table typically <15 feet

PRESUMPTIVE REMEDY ZONE 1

- Typical Cost \$500K to \$800K
- Conventional Excavation for Source Removal
- Large Dimensional Auger (LDA) Excavations for Source Removal
 - Clayey areas with deep water table
- Air Sparge (AS) Soil Vapor Extraction (SVE)
- Multi-Phase Extraction when product present
- Biosparge
- Chemical & Biological Injections



PRESUMPTIVE REMEDY ZONE 2 & 3

- Typical Cost \$500K to \$1M
- LDA Excavations for Source Removal
 - Clayey areas with deep water table
- Conventional Excavations for Source Removal
 Shallow water table and coastal areas
- AS SVE and MPE when product present
- Horizontal Wells
- Chemical & Biological Injections
- Biosparge



PRESUMPTIVE REMEDY ZONE 4

- Typical Cost \$400K
- Conventional Excavations for Source Removal
 - Shallow water table and coastal areas
- AS SVE
- MPE when product present
- Biosparge
- Chemical & Biological Injections





- Pilot Testing
- Additional Sampling
- Incorporate Site Specific Considerations
 - Regulatory Requirements For Each Media
 - Active Systems
 - -Passive Systems
 - -System Location
- On Site Zero To A Few Days




FREE PRODUCT REMEDIATION

- Bailer
- Sorbents
- Skimmers
- Vacuum Truck
- Multi-Phase Extraction



Bailer With Free Product





Sorbents And Passive Skimmer






Solar Powered Skimmer





Solar Skimmer Schematic

Single Well Using REM2500ES Remote Solar Station





Vacuum Truck





Soil Remediation

- Conventional Excavation
- Large Diameter Auger (LDA) Excavation
- Soil Vapor Extraction (SVE)



CONVENTIONAL EXCAVATION





SHEET PILING





SHEET PILING INSTALLED





LDA SUPPORT COLUMNS





LARGE DIAMETER AUGER





PORTABLE CONCRETE PLANT





FILLING WITH FLOWABLE FILL






OVERLAPPING LDA HOLES





LDA BORING CONVERTED TO WELL






GROUNDWATER REMEDIATION

- Air Sparge and Vapor Extraction
- Pump and Treat
- Bioremediation
- Chemical Oxidation



AIR SPARGING AND SOIL VAPOR EXTRACTION SCHEMATIC





SVE SYSTEM





AIR SPARGE SYSTEM






TREATMENT SYSTEM TRAILER





GROUNDWATER EXTRACTION SCHEMATIC






TREATMENT SYSTEM WITH TRAY STRIPPER





CHEMICAL OXIDATION OR BIOREMEDIATION SCHEMATIC



SCHEMATIC OF SOIL VADOSE ZONE INJECTION SYSTEM WITHIN THE OIL BURN LETTERKENNY ARMY DEPOT



CHEMICAL INJECTION SYSTEM



IN-SITU CHEMICAL OXIDATION

- Hydrogen Peroxide/Fenton's Reagent
- Hydrogen Peroxide/Chelated Iron Catalyst
- Potassium or Sodium Permanganate
- Sodium Persulfate
- Ozone/Hydrogen Peroxide plus Ozone
- Calcium/Magnesium Peroxide



POTASSIUM PERMANGANATE





HYDROGEN PEROXIDE





OTHER CHEMICAL OXIDATION

Sodium Persulfate

- -Activated with heat or ferrous salts
- Relatively long lasting (hours to weeks)
- Ozone
 - -Gas generated on site
 - -Short life span (minutes to hours)

Calcium Peroxide

- -Works at neutral to basic pH
- -Very long lasting
 - (weeks to months)
- -Encourages biological activity



BIO INJECTION SYSTEM





BIOREMEDIATION

- Aerobic vs. Anaerobic
- Biostimulation
 - Add nutrients, oxygen, etc. to stimulate existing microbes
 - Molasses, edible oil, lactate, magnesium peroxide
- Bioaugmentation
 - Add microbes, either natural or genetically engineered
 - Dehalococcoides, gene expression factor
- Natural Attenuation



- Typically Quarterly site visits to collect system and groundwater samples
- During remediation to evaluate progress
- One year post remediation to demonstrate target levels are achieved
- System Restart/Reinjection if concentrations rebound



CLOSURE

- Typically one to five years to achieve
- \$20,000 to \$5 million
- Closure with Conditions
- Clean Closure
- Regulatory Approval Order



Your Full Service Local

Engineering Firm

Lance I. Robinson, PE

lirobinson@mactec.com 813-289-0750

THANK YOU

www.mactec.com